



**MORTAR  
RANGE**



**THE  
LEADERS'  
CHOICE**

**MORTAR**

# BLOCK GRIP ADHESIVE

# MORTAR

## Excellent Adhesive For Cured Blocks

It's a single-component thixotropic thin-bed fixing and jointing block grip adhesive. It contains an aggregate ratio of graded inert sand with cement and polymers for applications as a bond-gripping material in civil construction works. It is recommended for fixing and jointing AAC blocks, ALC blocks, cement mortar blocks, cellular concrete blocks, fly ash bricks and composite cement blocks.



### USAGE AREAS

- Overlay on brick or block as a fixing and jointing material in thickness [1 mm to 3 mm], thin-bed in external and internal walls




DOSAGE:	PACK SIZE:	BEST BEFORE
10 ltrs-11 ltrs of water for 40 kg	40 kg	12 months

# ENDURO PLAST

# MORTAR

## Ready Mix Plaster

Single component rendering mortar with a ratio of graded inert sand with cement and polymers for applications in civil construction works.



### USAGE AREAS

- Manual plastering of internal & external walls in the range of 5-20 mm
- Rendering of high build ceiling in a single pass of 5-20 mm thickness



DOSAGE:	PACK SIZE:	BEST BEFORE
6.0 - 7.0 ltrs of water for 40 Kg	40 Kg	6 months

# DURAFLOOR

# MORTAR


## FLOOR HARDENER

DURAFLOOR is a high-quality durable cementitious-based, non-metallic, non-oxidising concrete Floor Hardener, free from any organic impurities. This hard wearing dry shake powder is a well-manufactured, graded composition of select cement, additives, graded aggregates & polymers to ensure ease of placing and finishing. This is best-suited for residential, commercial and industrial floors to deliver a monolithic, high abrasion-resistant floor. The finished surface with Floor Hardener provides better impact resistance and also protects the surface from gas, oil and chemical attack owing to its non-skid, anti-slip properties.



### USAGE AREAS

- Application rate intended traffic use.
- General vehicular traffic - 3kg/m<sup>2</sup>; Medium vehicular traffic - 5kg/m<sup>2</sup>; Heavy vehicular traffic - 7kg/m<sup>2</sup>



COVERAGE:	PACK SIZE:	BEST BEFORE
General vehicular traffic - 3kg/m <sup>2</sup> ; Medium vehicular traffic - 5kg/m <sup>2</sup> ; Heavy vehicular traffic - 7kg/m <sup>2</sup>	25 Kg	6 months

# FLOORSCRETE

# MORTAR

## Ready to use Floor Screed

JSW Floorscrete is ideal as a final protective levelling screed over waterproofing coating, warehouse, parapet and work shop floors and as an underlayment for marble as well as large tile floorings.

### USAGE AREAS

- residential, commercial and industrial floors to deliver a monolithic, high abrasion-resistant floor



High compressive strength



Excellent adhesion



Chemical & Alkali resistance

DOSAGE:	PACK SIZE:	BEST BEFORE
Coverage For 25 Kg Bag - 11.25 - 12.5 Sqft @ 12 Mm thickness	25 kg	12 months



### REGISTERED OFFICE

JSW Centre, Bandra Kurla Complex, Near MMRDA Grounds, Bandra East, Mumbai 400 051

### MARKETED BY:

**JSW Green Cement Pvt. Ltd.** Babukhan Millenium, Centre, 6-3-1099/1100, No. 702, Block-A, Somajiguda, Hyderabad, Telangana, India, Pincode - 500 082

**Email:** [info@jswcement.in](mailto:info@jswcement.in) | **Website:** [www.jswcement.in](http://www.jswcement.in) | **Toll free:** 18002662661

SCAN HERE FOR TDS



SCAN HERE

