



Features



Sag Resistant



Water Resistant




**Better Adhesive
Bond Strength**

JSW TYLFIX TYPE 2

Tile Adhesive for Floor ,Wall & Tile on Tile

AREAS OF APPLICATION


JSW Tylfix Type 2 is a polymer modified cement based powder tile adhesive for fixing All types of ceramic tile, terracotta, pavers, brick vitrified tiles, glass. It is suitable for Flooring and walls, for internal applications & external shaded area, external area, dry & wet area, new construction & renovation, domestic applications, commercial applications.



Kitchen



Bathroom & Toilet



Commercial & Residential



Canteen & Pantry

6 BENEFITS

- Easy to use - just add water on site, ready to use.
- Ideal product for tile-on-tile applications on floor.
- Sag resistant formula: provides hassle-free application on vertical walls.
- Water resistant - suitable for wet areas.
- Good adhesive bond strength & bonds to various cement-based substrates.
- Low VOC - for healthy living.

BEST BEFORE

12 months for sealed pack when stored under cover, out of direct sunlight and dampproof condition.

COVERAGE

- Approx. 5 - 6 m² / 20 kg bag at 3 mm thickness (using 6 mm x 6 mm notch)
- ***Coverage will vary depending on trowel notch size, type, tile size and substrate smoothness and evenness.**

STANDARD COMPLIANCES

- **IS:15477:2019TYPE2'T'**

TECHNICAL SPECIFICATIONS

Properties	Results
Tentative mixing ratio (Powder: Water)	3.5 : 1 by volume; 1 : 0.22 by weight
Mixed density	1.7 - 1.9 kg/ ltr
Table flow	180 mm
Open time (IS 15477 : 2019)	Approx. 20 minutes
Adjustability (IS 15477 : 2019)	Approx. 20 minutes
Pot life	Approx. 120 minutes
Tensile adhesion strength as per Is15477 : 2019	≥ 0.5 N/ mm ²
Application temperature (substrates & materials)	5°C to 35°C
Adhesive thickness	3 - 12 mm
Setting/ trafficable time	24 hours

PACK SIZE

20 kg



JSW Cement

World's No.1 Eco Friendly Cement Company

MARKETED BY: JSW Green Cement Pvt. Ltd.
Babukhan Millenium Centre, 6-3-1099/1100, No. 702, Block-A, Somajiguda, Hyderabad, Telangana, India, Pincode - 500 082.

Email: info@jswcement.in | Website: www.jswcement.in | Toll free - 18002662661

