



TILE ADHESIVE, GROUT & CLEANER



Features



Non Shrink



Crack Free




Easily Pourable

TYLFIX GROUT- Cementitious

CEMENT-BASED TILE JOINT FILLER GROUT

AREAS OF APPLICATION


TYLFIX GROUT- Cementitious is a polymer-modified, cement-based tile joint filler grouting material, which is highly suitable for filling the joints/gap of all types of tiles. It exhibits water-resistant properties, making it an ideal choice for various applications.



Kitchen



Bathroom & Toilet



Commercial & Residential



Canteen & Pantry

4 BENEFITS

- **Easy to use & Clean:** just mix with water, ready to use
- **Polymer modified:** crack-free, minimum shrinkage & water resistance
- **Suitable for varied tile and stones:** All ceramics, vitrified tiles, granites, etc.
- **Low VOC:** For healthy living.

STANDARD COMPLIANCE/ SPECIFICATION

TYLFIX GROUT- Cementitious complies with the CG2W requirements as specified in "BS EN 13888:2009 - Requirements, evaluation of conformity, classification, and designation of grouts for tiles", as well as "ISO 13007- Part 3: Terms, definitions, and specifications for grouts."

BEST BEFORE

- 12 months for sealed pack when stored under cover, out of direct sunlight, damp-proof condition.
- Should be in a dry and covered area.

COVERAGE

- Coverage would dependent upon porosity & contamination of substrate.

SHADES

- * Available in Multi Smart Colours.

TECHNICAL SPECIFICATIONS

Properties	Results
Component Appearance	Cementitious Coloured Powder
Tentative Mixing Ratio	1 kg Tyifix Grout : 0.33-0.40 kg Water
(Tyifix Grout : Water)	(2.5-3 : 1 by weight)
Mixed Density	1.40 – 1.80 kg/ltr
Pot Life @ 27± 2° C	Min 45 minutes
Joint Width	Up to 3 mm
Application Temperature	10°C to 35°C
Light Foot Traffic	24 hours
Regular Traffic	7 Days
Final Curing Time	28 days

PACK SIZE

1 kg



World's No.1 Eco Friendly Cement Company

MARKETED BY: **JSW Green Cement Pvt. Ltd.**
Babukhan Millenium Centre, 6-3-1099/1100, No. 702, Block-A, Somajiguda, Hyderabad, Telangana, India, Pincode - 500 082.

Email: info@jswcement.in | **Website:** www.jswcement.in | **Toll free -** 18002662661

SCAN HERE FOR TDS



SCAN HERE



TYLFIX GROUT- Cementitious

TILE ADHESIVE, GROUT & CLEANER