TECHNICAL DATASHEET

TYLFIX CLEANER STRONG PERORMANCE CLEANER

DESCRIPTION

Tylfix Cleaner is a strong performance rapid active cleaner and degreasing solution for use on tiles, bathtubs, wash basin, privy basin and concrete etc. It is used to clean whitish spot/ layer as normally observed in the bathroom under plastic/ metal buckets (normal detergent is not helpful) with ease.

FEATURES AND ADVANTAGES

- · Easy to use just mix with water & clean the surface
- Fast & effective removes difficult stains easily fast & effective
- Degreases the tile surface easily for soaps, scum, efflorescence, mineral deposit
- Cleans all types of tiles like ceramic, porcelain, vitrified tiles
 and grout
- Protects the color & shine of tile
- Does not damage the joints between ceramic tiles, even those grouted with colored products

- AREA OF APPLICATION
- Floors and wall tilings in kitchens, bathrooms, toilets, garages, factories, general building sites & residential tilings. Internal & external tiling area. Domestic & commercial tiling area. Routing tile cleaning with mop in bathroom & other tiling area.

AREA OF USE

Surfaces to be cleaned

Ceramic tiles, glazed tiles, porcelain tiles, vitrified tiles, glass mosaic tiles & sanitary ware. Cleaning moss and wax from concrete and ceramics. Surfaces before & after application of epoxy products. Natural stones.

APPLICATION INSTRUCTIONS

- For mild blemish spots/layers, mix JSW Tylfix Cleaner with water with 1:1 proportion
- · Soak the cloth or sponge in the diluted solution and rub the surfaces till the spots/layers are removed
- For stubborn spots/layers, neat JSW Tylfix Cleaner liquid (without mixing with water) should be used for cleaning, make sure to check this in small areas before cleaning the complete area
- For routine tile cleaning, dilute two capfuls of Tylfix cleaner with half a bucket of water & use diluted solution for cleaning the tiles & sanitary ware

LIMITATIONS

Check JSW Tylfix Cleaner before using for cleaning of coloured concrete, granite, marble stone flooring & other stones with corner tests, because it may etch the surface. (If the stone shows discoloration up to 24hrs after application, do not use product).

STANDARD COMPLIANCE/SPECIFICATION

JSW Tylfix Cleaner complies to Class 2 requirements as per "IS 13630 part 8:2006 - Method of test, sampling & basis for acceptance for determination of Stain and Chemical Resistance of glazed tiles"





TECHNICAL DATASHEET



TYLFIX CLEANER STRONG PERORMANCE CLEANER

TECHNICAL DATA

PARAMETERS	RESULTS	
Appearance	Color to be checked	
Density	1.02 + 0.02 kg/ltr	
Viscosity	Equal to water	
Soaking time	5 minutes	
Dilution with water	Depend upon substrate condition & stain severity	

RESISTANCE TO STAINING RATIO IS 13630 PART 8:2006 (1:1 DILUTION WITH POTABLE WATER)

PARAMETERS	RESULTS	
Pickle	Passes	
Turmeric	Passes	
Wine	Passes	
Oil	Passes	
COVERAGE		PACK SIZE
 Coverage would dependent upon porosity & contamination of substrate. 		• 1 ltr & 5 ltr packs

BEST BEFORE

 12 months for sealed pack when stored under cover, out of direct sunlight, damp-proof condition and protect from extremes of temperature.

SAFETY PRECAUTIONS

- Keep away from children
- Wear suitable protective clothing, gloves and eyes/face protection
- · After contact with skin, wash immediately with plenty of clean water
- In case of contact with eyes rinse immediately with plenty of clean water and seek medical advice Limited to professional use only. For more details please refer the relevant material safety data sheet, available on request

Disclaimer: JSW construction chemical dry mix products are guaranteed against material and manufacturing defects. The product is sold as per standard terms and conditions of sales, copies of which may be obtained on request. JSW's endeavor is to ensure correct and accurate information on product performance and recommended specifications as mentioned in literature, and still may have to abstain from circumstantial deviations which are beyond control due to human intervention, atmospheric conditions or natural calamities which may not be in accordance with any advice, specification, recommendation or information given by it.

MARKETED BY: **JSW** Green Cement **Pvt.** Ltd. Babukhan Millenium Centre, 6-3-1099/1100, No. 702, Block-A, Somajiguda, Hyderabad, Telangana, India, Pincode - 500 082.

