



JSW PSC Cement

THE LEADERS' CHOICE

TEST CERTIFICATE

Portland Slag Cement as per IS 455:2015

REF.: JSW/QA/2023/A-01 DATE: 24-09-2022

WEEK NO.: **34** 20-08-2023 26-08-2023

CHARACTERISTIC	RESULTS OBTAINED	REQUIREMENT OF IS 455:2015
(A) CHEMICAL COMPOSITION		
(i) Magnesia (MgO), % by mass	5.19	10.0 Maximum
(ii) Insoluble Residue, % by mass	0.43	4.0 Maximum
(iii) Sulphuric Anhydride (SO ₃) % by mass	2.12	3.5 Maximum
(iv) Sulphide Sulphur (S)	0.22	1.5 Maximum
(v) Loss on Ignition % by mass	0.86	5.0 Maximum
(vi) Total Chloride (CI), % by mass	0.014	0.10 Maximum
(B) PHYSICAL TESTING		
1. Fineness of Cement		
Sp.Surface (m²/kg)	362	225 m ² /kg minimum
2. Soundness		
Le-Chatelier Expansion (mm)	1.00	10 mm Maximum
Autoclave Expansion (%)	0.047	0.8 % Maximum
3. Setting Time		
Initial (in Minutes)	205	Not less than 30 minutes
Final (in Minutes)	260	Not more than 600 minutes
4. Compressive Strength (MPa)		
(a) At 72 ± 1 Hr.	25.34	16 MPa Minimum
(b) At 168 ± 2 Hrs.	32.54	22 MPa Minimum
(c) At 672 ± 4 Hrs.	44.37	33 MPa Minimum
5. Normal Consistency	31.50	
6. GGBS addition (%)	55.00	25% MIN & 70% MAX

Remarks:

- 1. Temperature during testing $27 \pm 2^{\circ}$ c.
- 2. Portland Slag Cement conforms to the requirement of IS 455:2015 in all respects.
- 3. Specific Gravity :- 3.05

Address:

JSW CEMENT LIMITED

Village- Khar Karavi, Post - Gadab Taluka- Pen, District- Raigad,PIN- 402107

Maharashtra. +91 2143 277601/2

Prepared By Officer-QC

Frak

Checked By SH -QC

Approved By HOD-QC