



**TYLFIX
RANGE**



**THE
LEADERS'
CHOICE**

**TILE ADHESIVE,
GROUT AND CLEANER**

JSW TYLFIX TYPE 1

TYLFIX RANGE

Tile Adhesive for Floor & Wall Ceramic Tiles

JSW Tyfix Type 1 is a polymer modified cement based powder tile adhesive for fixing all type of ceramic, clay tiles, It is suitable for both vertical and horizontal application. It gives excellent bond on exterior cementitious surfaces like plaster or concrete etc.

USAGE AREAS

- All types of ceramic tiles and bricks are vitrified as recommended to fix on the floor.
- Cement-based screeds, plasters, mortars, concrete surfaces and bricks.



Easy to Use



Water Resistant



Better Adhesive
Bond Strength



POT LIFE	PACK SIZE:	BEST BEFORE
Approx. 60 minutes	20 kg bag	12 months

JSW TYLFIX TYPE 2

TYLFIX RANGE

Tile Adhesive for Floor & Wall & Tile on Tile

JSW Tyfix Type 2 is a polymer modified cement based powder tile adhesive for fixing All types of ceramic tile, terracotta, pavers, brick vitrified tiles, glass. It is suitable for Flooring and walls, for internal applications & external shaded area, external area, dry & wet area, new construction & renovation, domestic applications, commercial applications.

USAGE AREAS

- All types of ceramic tiles, terracotta, pavers, brick-vitrified tiles, glass mosaic tiles.
- Cement-based screeds & mortars, cement-based plasters/ renders, concrete surfaces, bricks,



Sag Resistant



Water Resistant



Better Adhesive
Bond Strength



POT LIFE:	PACK SIZE:	BEST BEFORE
Approx. 120 minutes	20 kg bag	12 months

COLOUR AVAILABLE

- Available in Grey & White colour

JSW TYLFIX TYPE 3

TYLFIX RANGE

Tile Adhesive for Glass & Stone Tiles

JSW Tyfix Type 3 is a polymer modified cement based powder tile adhesive for fixing All types of ceramic tiles, clay tiles, basalt tiles, terracotta, pavers, brick, vitrified tiles, glass mosaic tiles, porcelain tiles and all natural stone tiles.

USAGE AREAS

- All types of ceramic tiles, clay tiles, basalt tiles, terracotta, pavers, brick, vitrified tiles, glass mosaic tiles, porcelain tiles and all natural stone tiles.



Sag Resistant



Water Resistant



Better Adhesive
Bond Strength



POT LIFE:	PACK SIZE:	BEST BEFORE
Approx. 120 minutes	20 kg bag	12 months

COLOUR AVAILABLE

- Available in Grey & White colour

JSW TYLFIX TYPE 4

TYLFIX RANGE

Tile Adhesive for large Glass & Stone Tiles and Dry Wall Boards

JSW Tyfix Type 4 All types of ceramic tiles, clay tiles, basalt tiles, terracotta, pavers, brick, vitrified tiles, glass mosaic tiles, porcelain tiles, natural stone tiles, large format tiles, marble, large thin/slim tiles, low thickness slabs.

USAGE AREAS

- All types of ceramic tiles, clay tiles, basalt tiles, terracotta, pavers, bricks, vitrified tiles, glass mosaic tiles, porcelain tiles, natural stone tiles, large format tiles, marble, large thin/slim tiles, low thickness slabs.



Heat Ageing



Water Resistant



Better Adhesive Bond Strength

COLOUR AVAILABLE

- Available in Grey & White colour



POT LIFE:	PACK SIZE:	BEST BEFORE
Approx. 120 minutes	20 kg	12 months

TYLFIX GROUT - Cementitious

TYLFIX RANGE

Cement-based Tile Joint Filler Grout

JSW Tyfix Grout - Cementitious is a polymer-modified, cement-based tile joint filler grouting material, which is highly suitable for filling the joints/gap of all types of tiles. It exhibits water-resistant properties, making it an ideal choice for various applications.

USAGE AREAS

- All types of ceramic tile, glazed tiles, porcelain tiles, vitrified & fully vitrified tiles, natural stone, and glass mosaic tiles.



Non Shrink



Crack Free



Easily Pourable



POT LIFE	PACK SIZE:	BEST BEFORE
Min. 45 minutes	1 kg	12 months

TYLFIX CLEANER

TYLFIX RANGE

Strong Performance Cleaner

Tyfix Cleaner is a high quality rapid active cleaner and degreasing solution for use on tiles, bathtubs, wash basin, privy basin and concrete etc. It is used to clean whitish spot/ layer as normally observed in the bathroom under plastic/ metal buckets (normal detergent is not helpful) with ease.

USAGE AREAS

- Ceramic tiles, glazed tiles, porcelain tiles, vitrified tiles, glass mosaic tiles & sanitary ware. Cleaning moss and wax from concrete and ceramics. Surfaces before & after application of epoxy products. Natural stones.



Easy Cleaning



No Residual Mark



Cleans all types of Tiles



SOAKING TIME	PACK SIZE:	BEST BEFORE
5 minutes	1 Ltr, 5 Ltr	12 months

TYLFIX EXPOXY GROUT

TYLFIX RANGE

EPOXY BASED JOINT FILLER

TYLFIX EXPOXY GROUT is a three-component color-fast, stain and chemical resistance, hard wearing and impervious tile joint epoxy resin-based grout specifically designed for use in application of ceramic tiles, vitrified tiles, semi-vitrified tile, glass mosaic tiles, metal tiles, precast terrazzo, engineered stone floors and natural stone joints where a hygienic and sterile condition is expected. It is well suited for interior and covered exterior floor and wall of residential and commercial applications. It effectively fills the gaps and levels itself to give a hard-wearing, dust & water proof tile joint.



USAGE AREAS

- All types of ceramic tiles, clay tiles, basalt tiles, terracotta, pavers, bricks, vitrified tiles, glass mosaic tiles, porcelain tiles, natural stone tiles, large format tiles, marble, large thin/slim tiles, low thickness slabs.



Non Shrink



Decorative and Glossy Finish



Extremely durable and completely waterproof

POT LIFE:	PACK SIZE:	BEST BEFORE
Approx. 120 minutes	20 kg	12 months

JSW TYLFIX TYPE 5

TYLFIX RANGE

PU ADHESIVE FOR CERAMIC TILES AND STONE MATERIAL

JSW Tylfix Type 5 PU is Two-component, PU Resin Based, high-performance, polyurethane adhesives is an improved (2) reaction adhesive (R) classified as class R2T. It is a high performance, PU resin based multipurpose tile adhesive for fixing ceramic tiles marble, stone cladding and brick slips in interior or exterior situations.

USAGE AREAS

- All types of ceramic tiles, clay tiles, basalt tiles, terracotta, pavers, bricks, vitrified tiles, glass mosaic tiles, porcelain tiles, natural stone tiles, large format tiles, marble, large thin/slim tiles, low thickness slabs.



High adhesive bond strength



Long open time



Flexible

POT LIFE:	PACK SIZE:	BEST BEFORE
Approx. 120 minutes	20 kg	12 months



REGISTERED OFFICE

JSW Centre, Bandra Kurla Complex, Near MMRDA Grounds, Bandra East, Mumbai 400 051

MARKETED BY:

JSW Green Cement Pvt. Ltd. Babukhan Millenium, Centre, 6-3-1099/1100, No. 702, Block-A, Somajiguda, Hyderabad, Telangana, India, Pincode - 500 082

Email: info@jswcement.in | **Website:** www.jswcement.in | **Toll free:** 18002662661

SCAN HERE FOR TDS



SCAN HERE

