







Features



Excellent Adhesion



Anti Efflorescence



Good Crack Bridging Ability



Waterproofing Flexible Coating

SMARTBLOK CEM 2K ULTRA

High Performance Acrylic Cementitious Waterproofing Coating


AREAS OF APPLICATION

JSW SmartBlok Acrycem 2K is a two-component water proofing product, based on acrylic and cementitious materials. It forms an excellent flexible film coating on the concrete and mortar substrate, that provides superior water proofing









Terrace

Wet Areas

OH / UG water tanks

Below grade structures

4 BENEFITS

- Flexible Film: It forms flexible film coating that accommodates cracks and provide better hiding on the surface.
- Water Resistance: It provides excellent resistance to water uptake.
- Adhesion: It exhibits superior adhesion to concrete and masonry surfaces.
- Eco-Friendly: It is composed of eco-friendly materials with low VOC.

DOSAGE

• Liquid Polymer Part: Powder Part = 1:2 (by weight).

BEST BEFORE

- 12 months from the date of manufacturing.
- Store in cool and dry place in unopened condition. Prevent from direct sunlight.

TECHNICAL SPECIFICATIONS

Description	Results
Nature/Appearance	Two component (1 part liq. Polymer + 2 part powder)
Appearance	Liquid Part: Milky White Powder: Grey
Wet mix slurry density	1.5-1.6 g/cc
pH of slurry	9-11
Pot life of the Mix at 30 °C	Minimum 45 min.
Elongation at break of dry film	Minimum 60%

COVERAGE

- 7-8 Sq.ft/Kg for 2 Coats
- Note:- Coverage area will vary depending upon the Substrate undulations & porosity.

PACK SIZE

15 kg 30 ka





World's No.1 Eco Friendly Cement Company



