



ENDURO PLAST



## Features



Less water consumption



Increase in durability



Reduce Rebound losses

# ENDURO PLAST

READY MIX PLASTER

## AREAS OF APPLICATION

Single component rendering mortar with a ratio of graded inert sand with cement and polymers for applications in civil construction works.



For Walls



For Ceilings

## 12 BENEFITS

- Cohesive & workable mortar
- Less water consumption
- Increased Curing efficiency
- Improves bond strength with applied substrate
- Reduce Rebound losses
- Better tensile and flexural strength
- Increase in durability
- Faster rate of application
- Extended application time
- Uniform and smooth finishes
- Reduces wall porosity & voids
- Provides enhanced coverage and saves material

## SHELF-LIFE AND STORAGE

- 6 months from date of manufacturing, when stored in a dry & sealed condition.

## COVERAGE

- **For Walls** - In w/p ratio of 0.14-0.16 to provide thickness of 5-20 mm, at a coverage of 0.175 TO 0.20 Kg/sqft/mm.
- **For Ceilings** - In w/p ratio of 0.14-0.16 to provide thickness of 5-20 mm, at a coverage of 0.175 to 0.20 Kg/sqft/mm.
- **Water Demand** - 6.0 - 7.0 ltrs for 40 Kg

## TECHNICAL SPECIFICATIONS

Properties	Results
Pot life at 30°C min	90-120
Compressive Strength at 28 days, Mpa	6-8
Tensile Strength at 28 days, Mpa	Min.1.0
Flexural Strength at 28 days, Mpa	Min.1.5
Water Absorption%	Max 5
Rebound Loss %	Max 2

## PACK SIZE

40 kg



# JSW Cement

World's No.1 Eco Friendly Cement Company

MARKETED BY: JSW Green Cement Pvt. Ltd.  
Babukhan Millenium Centre, 6-3-1099/1100, No. 702, Block-A, Somajiguda, Hyderabad,  
Telangana, India, Pincode - 500 082.

Email: [info@jswcement.in](mailto:info@jswcement.in) | Website: [www.jswcement.in](http://www.jswcement.in) | Toll free - 18002612661



ENDURO PLAST

MORTAR