



MICRO CONCRETE



## Features



Highly flowable



Negligible wastage



Nil shrinkage

# JSW MICRO CONCRETE

High Strength Non Shrink Micro Concrete

## AREAS OF APPLICATION

**JSW Micro Concrete** is cementitious polymer modified, high performance, high strength, non-shrink material specially designed for micro concreting and jacketing applications of repair areas where the concrete has deteriorated.

## 9 BENEFITS

- Single Component, Easy to use - just water to be added at site,
- Highly flowable
- Can easily reach the rare corner of the structure
- Uniform and smooth finish
- Early de-shuttering
- High ultimate strength and durable
- Faster completion of work
- Negligible wastage
- Nil shrinkage

## SHELF-LIFE AND STORAGE

12 months from the date of manufacturing if stored in unopened original packing, under shade in dry and moisture free conditions.

## COVERAGE

- Coverage For 25 Kg Bag - 11.25 - 12.5 Sqft @ 12 Mm thickness

## TECHNICAL SPECIFICATIONS

Properties	Results
Appearance	Free Flowing Powder
Color	Cementitious Light Grey
Fresh wet density	2200 – 2300 kg/m <sup>3</sup>
Water powder ratio	0.10 – 0.12 by weight
Pot life	30 Mins at 27°C
Compressive strength @ 28 days	Min 50 Mpa
Shrinkage	Nil
Yield	12 Ltrs / Pack of micro concrete (25 Kg)

## PACK SIZE

25 kg



**World's No.1 Eco Friendly Cement Company**

MARKETED BY: JSW Green Cement Pvt. Ltd.  
Babukhan Millenium Centre, 6-3-1099/1100, No. 702, Block-A, Somajiguda, Hyderabad,  
Telangana, India, Pincode - 500 082.

Email: [info@jswcement.in](mailto:info@jswcement.in) | Website: [www.jswcement.in](http://www.jswcement.in) | Toll free - 18002612661

SCAN HERE FOR TDS



SCAN HERE



MICRO CONCRETE

MORTAR