



PRECISION STEEL GROUTS



Features



Consistent quality



Faster completion
of work



Nil shrinkage

STEEL GROUT - GUN GRADE


PUMPABLE GUN GRADE MORTAR FOR TIE - ROD HOLE APPLICATION

AREAS OF APPLICATION

JSW SteelGrout - Gun Grade Mortar is recommended for filling of tie rod hole/slit holes in concrete and natural stones.



Filling of Tie Rod Hole



Slit Holes

9 BENEFITS

- Single Component, Easy to use - just water to be added at site,
- Consistent quality
- Waterproof of joints/holes
- Non-curing and binds better to substrate
- Uniform and smooth finish
- Convenient to apply
- Faster completion of work
- Negligible wastage
- Nil shrinkage

BEST BEFORE

12 months from the date of manufacturing if stored in unopened original packing, under shade in dry and moisture free conditions.

COVERAGE & CLASS

- Always add powder to water.
- Do not add excess water than recommended.
- Coverage per Kg @ 6 mm dia holes*

PACK SIZE

25 kg



World's No.1 Eco Friendly Cement Company

TECHNICAL SPECIFICATIONS

Properties	Results
Appearance	Free Flowing Powder
Color	Cementitious Light Grey
Bulk density	1450-1550 Kg/cum
Water powder ratio	25-27 % by weight
Pot life	90 mins @ 27°C
Compressive strength @ 28 days	8 - 10 Mpa
300 mm depth	Cylindrical holes 13-14 holes
Shrinkage	Nil
Water curing	Self curing
Flexural strength @ 28 days	2-3 MPa



STEEL GROUT - GUN GRADE

PRECISION STEEL GROUTS

MARKETED BY: JSW Green Cement Pvt. Ltd.

Babukhan Millenium Centre, 6-3-1099/1100, No. 702, Block-A, Somajiguda, Hyderabad, Telangana, India, Pincode - 500 082.

Email: info@jswcement.in | Website: www.jswcement.in | Toll free - 18002662661

SCAN HERE FOR TDS



SCAN HERE

